



theuvcentre.com

1 pages

Revised edition No. 1.2

Date 28/04/2011

100% ACRYLIC EMULSION WHITE UNDERCOAT FOR FLUORESCENT DATA SHEET

Features:

A water based 100% pure acrylic emulsion, exhibiting excellent exterior durability, suitable for application to a wide range of substrates. Contains a high proportion of titanium dioxide, thus giving excellent reflective and non-fade properties. To be used as a basecoat for WB42 Acrylic Fluorescent Paint.

Availability:

5, 2.5 and 1 Litre containers.

Volume Solids:

45% \pm 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Previously painted surfaces must be stripped, thoroughly rubbed down with abrasive paper and cleaned prior to application.

Application:

Brush, roller, conventional or airless spray. Use clean tap water for thinning, if required and cleaning. It is recommended that two coats are applied to previously untreated surfaces, allowing 2 hours drying between coats.

Coverage:

Approximately 50 sq metres per 5 Litres depending on porosity of substrate.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

For COSHH & MSDS Information, please download Fluorescent Coatings COSHH & MSDS Information from our website: www.theuvcentre.com