



theuvcentre.com

1 pages

Revised edition No. 1.2

Date 28/04/2011

## 100% ACRYLIC EMULSION FLUORESCENT DATA SHEET

### Features:

A water based 100% pure acrylic fluorescent finish. A special range of vivid safety marking paints ideal for use in poorly lit areas. Suitable for application to a wide range of substrates after suitable priming with WBP42 Basecoat. Requires a source of daylight, moonlight or artificial light to be effective.

### Availability:

Colour range: Yellow, Blue, Orange, Scarlet and Green in 5, 2.5 and 1 Litre containers in a Matt finish.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

### Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Apply over WBP42 Fluorescent Basecoat White.

### Application:

Brush, roller, conventional or airless spray. Supplied ready for use for brushing. Use clean tap water for thinning, if required and cleaning. It is recommended that two coats be applied to primed surfaces, allowing 2 hours drying between coats. Must be over coated with WBS42/70/4 Clear Overcoat.

### Coverage:

Approximately 50 sq metres per 5 Litre, depending on porosity of substrate.

### Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.

See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

**For COSHH & MSDS Information, please download Fluorescent Coatings COSHH & MSDS Information from our website: [www.theuvcentre.com](http://www.theuvcentre.com)**